

Oceanspace S6800E



Huawei Symantec



Oceanspace S6800E

Huawei Symantec Oceanspace S6800E is an industry-leading storage product designed for the mid-range and high-end storage markets. The S6800E offers a full range of features such as high density, FC and iSCSI connectivity, modular ports, and multi-level data protection mechanism. It ensures data integrity and service continuity while meeting the requirements of large databases, high performance computing, online transaction processing (OLTP), centralized storage, data migration, data backup, and disaster recovery.

Product Features

High Performance

- **64-bit multi-core architecture:** The S6800E delivers enhanced processing capability with 64-bit multi-core processors, 64-bit dual-channel memory modules, 64-bit 10 Gb/s system buses, and 64-bit real-time operating systems.
- **Solid state drives (SSDs):** Significantly increases overall performance of the S6800E.
- **Application-oriented patented I/O algorithm:** Dynamically adjusts the read/write mode of hard disks according to the read/write mode of the hosts.
- **Dynamic load balancing:** The two hot-backup controllers of the S6800E execute I/O operations concurrently while mirroring the write cache of each other with two dedicated channels.

Robust Reliability

- **Built-in UPS:** Protects data against power failure with the built-in UPS.
- **Pre-copy technology:** Prevents data loss with advanced faulty disk detection.
- **Bad sector repair:** Prolongs the service life of hard disks by lowering the failure rate by 50%.
- **Global hot spare:** Acts as the hot backup for data disks in the storage system.
- **Advanced data protection technologies:** Boosts data protection with the value-added features:
The controller cache mirroring mechanism improves data availability. **HyperImage** generates real-time snapshots of online data so that data can be restored from the snapshots instantly. HyperImage

can also generate multiple point-in-time snapshots to provide continuous data protection.

HyperCopy, an across-platform volume copy technology, enhances data protection among heterogeneous storage devices.

HyperMirror implements remote disaster recovery.

Reduced TCO

- **Modular ports:** The combination of FC and iSCSI host ports enables an FC+IP SAN.
- **High disk density:** 1U space can house six hard disks. An expansion disk enclosure can house 24 hard disks, lowering the expansion cost by 60%.
- **Tiered storage:** Delivers higher performance at a lower cost by moving data among multiple storage tiers (SATA, FC, and SSD).
- **User-friendly management and maintenance designs:** Simplifies the management through web-based GUI and programmable CLI, and reduces operational and maintenance costs with fault alarming by SMS, email, sound and light.

Low Power Consumption

- **Energy-saving hard disks:** Lowers power consumption by more than 40% with automatic spin-down or speed-down of hard disks.
- **High-speed air cooling:** Doubles the air cooling efficiency with an advanced hydromechanics design.
- **Intelligent fan control:** Enables the S6800E adaptable to environment changes and lowers system power consumption by nearly 15%.

Oceanspace S6800E



Huawei Symantec

Technical Specifications

Model	S6800E
Basic Specifications	
Architecture	Dual-controller (active-active)
Processor	64-bit multi-core CPU
Cache	32 GB
Number of host ports	Twelve 4 Gb/s FC ports, or four 4 Gb/s FC ports + 4 GE ports, or twelve 8 Gb/s FC ports, or four 8 Gb/s FC ports + four 10GE ports
Number of hard disks	480
Disk specifications	SATA disk: 1 TB/2 TB (7,200 rpm)
	FC disk: 300 GB/450 GB/600 GB (15,000 rpm)
	SSD: 100 GB/200 GB
Disk density	24 bays per enclosure
Number of host connections	512
LUNs	4,096
RAID	
RAID level	0, 1, 3, 5, 6, 10, 50
Reliability	
Parts redundancy	Controllers, power supplies, fans, UPSs, expansion disk enclosures
Disk protection	Global hot spare, disk pre-copy, bad sector repair, disk health analysis (DHA)
Power failure protection	Coffer, built-in UPS
Host Compatibility	
Operating system	Windows, Linux, Solaris, HP-UX, AIX, FreeBSD, MAC OS X
Others	VMware, Hyper-V, XenServer
Software	
Host multipathing	UltraPath (Windows/Linux/AIX), STMS (Solaris), PV-Links (HP-UX)
Value-added software	HostAgent, HyperImage, HyperCopy, HyperMirror/A, HyperMirror/S
Regulation compliance	WORM
Management	
Management method	ISM
Fault alarming	ISM display, SMS, email, SNMP, sound and light
Remote management	Remote access through Web or dial-up modem
Physical Characteristics	
Power supply	200 V to 240 V AC (50/60 Hz), -48 V to -60 V DC
Power consumption (controller enclosure)	AC: < 860 W
	DC: < 800 W
Power consumption (disk enclosure)	AC: < 670 W
	DC: < 620 W
Dimensions (H x W x D)	4U, 175 mm x 446 mm x 600 mm
Weight	Controller enclosure: < 45 kg
	Disk enclosure: < 38 kg

About this publication

The information contained in this document is for reference purpose only, do not constitute the warranty of any kind, express or implied. It is subject to change or withdrawal according to specific customer requirements and conditions.

All the trademarks, pictures, and brands mentioned in this document are the property of Huawei Symantec Technologies Co., Ltd or their respective holders.